Rhino 2000 Rack

Designed using the most up to date technologies, the On-Line operating systems have been developed with the clear objective of increasing all the quality and reliability parameters to the maximum, by reducing the system to a minimum size and transforming it into one of the most competitive on the market thanks to its quality, safety and ergonomics.

Potencia (W)	1400
Line in tension	230 V +/- 25%
Line out tension with line in tension	230 V +/- 2%
Line out signal / Line in tension	Sinus Wave
Type of battery	72v
Cycle of life	10´
90% battery charge time	8 hours
Communication interface	Contacts/RS232
Technology	On line,double conversion

Technical Information

Technical specifications:

• On-line technology double conversion power. Professional Protection.

• Perfect permanent sine wave. Filtered anda regulated continuous signal.

• Built in By-Pass system.

• Advanced diagnostic panel.

• Protection for telephone line RJ45 (telf. / fax / ADSL / Networking).

• Up to six independent outputs (according to the model).

• Possibility of creating a protected dedicated line for multiple stations.

• Ideal for use in multi feature servers.

• Available in rack format.

• Low consumption.

• RS 232 communication port for the PC.

• Software "DATA SAVER" with automatic shutdown in the case of power cut. Package contents:

• UPS Rhino

• Cables

• User´s manual (7 languages)

• 2 years warranty card

Shiping Information

	Contains
Unity	1
Intermediate box	-
Export carton	1
Pallet	

System Requirements

Windows vista, XP or 2000

USB Port

512 MB RAM

PIII or Higuer

	Unity	Intermediate box	Export carton
EAN	8436001287706	-	8436001287706
Weight	36.3	-	36.3
Widht	0.27	-	0.27

Depth	0.69	-	0.69
Warranty	3 years		
ID de FCC/FC			